

Alfa 314 Spot Welder

AC - Medium Frequency 1000 Hz
Pneumatic Or Electric Drive

ProSpot

welding & joining technologies



Equipment:

- Pneumatic circuit with single pressure system
- I/O water valves 3/4"
- Air Inlet valve 3/4"
- Electric pedal
- Isolator
- Adjustable hydraulic jack in lower arm

Optionals:

- Circuit breaker (incorporated in MF welders)
- Servo driven head. Force 1500 daN
- Proportional valve
- Flowmeter
- Pneumatic circuit with counterpressure system
- Double stroke (80+40) for 750 daN
- Transformer 300 kVA (50Hz)



MFC-3000

Medium Frequency Inverter with adaptative controller

Technical features

Main Voltage	V	400 (50 Hz)
Electrode diameter (conical 10°)	mm	24
Electrode holder diameter	mm	40
Arms diameter	mm	80
Distance between arms min-max	mm	140-500
Approach /welding stroke	mm	0/120
Manoeuvres / minute (10 mm)	min-1	90

Alfa 314 - Machine Codes		A3141	A3144	A3146	A3241	A3244	A3246	A3341	A3344	A3346
Welding frequency	Hz	50	1000	1000	50	1000	1000	50	1000	1000
Power at 50 % D.C.	kVA	200	170	340	200	170	340	200	170	340
DIN throat depth	mm	400	400	400	600	600	600	750	750	750
Force at 6 bar	daN	1400	1400	1400	1400	1400	1400	1400	1400	1400
Max. short circuit current (5 periods)	kA	60	45	80	50	42	72	40	38	64
Max. welding current (5 periods)	kA	48	45	80	40	42	72	32	38	64
Air consumption at 50 mm / 6 bar	NI	8,4	8,4	8,4	8,4	8,4	8,4	8,4	8,4	8,4
Cooling water consumption	l/h	360	720	720	360	720	720	360	720	720
Lower arm	-	-			•	•	•	•	•	•
Admissible power	kVA	500	250	500	500	250	500	500	250	500
Delayed fuses	A	500	250	500	500	250	500	500	250	500
Main supply section by phase	mm2	240	120	240	240	120	240	240	120	240
Secondary voltage	V	8,5/10,5	10,0	10,0	8,5/10,5	10,0	10,0	8,5/10,5	10,0	10,0
Width	mm	640	640	640	640	640	640	640	640	640
Length	mm	1600	1600	1600	1800	1800	1800	1950	1950	1950
Heigh	mm	2333	2333	2333	2333	2333	2333	2333	2333	2333
Weight	Kgs	870	800	820	910	830	880	950	850	900
Medium Frequency Inverter MFC-3015	nr	-	1	2	-	1	2	-	1	2



Prospot Limited - Unit C Riverside Industrial Estate
Atherstone Street - Fazeley - Tamworth - Staffordshire - B78 3RW
Telephone: 01827 254 829 - Fax: 01827 254 832
Email: sales@prospot.co.uk - Web: www.prospot.co.uk